



## CK7210X1SP

### Gastronorm Counter

#### Product Features

- Fully automatic
- Controller with Bluetooth and NFC connectivity
- HACCP compliant data export
- Adjustable shelves
- Self-closing doors
- High quality catering grade 304 stainless steel
- Accepts Gastronorm pans (not supplied)
- Splashback
- 1/1 Gastronorm cupboards
- Castors, 2 lockable
- Replaceable door gasket

Stainless steel counter chiller with GN1/1 shelves

The CK7210X1SP is made for professional kitchens, and it offers an ideal solution for keeping ingredients chilled and within easy reach during service. It has a 48% lower energy consumption compared to the previous CK7210 model. It is made from durable SS304 stainless steel and features automatic defrost and GN1/1 dimensioned shelves for easy cleaning and smooth workflows. Its ventilated cooling system keeps contents at a consistent temperature, and the electronic controller makes it easy to adjust the temperature to fit your ingredients. The controller has NFC connectivity and Bluetooth. This means that you via an app can control the lighting, check the temperature of the cabinet, and even easily export data for reporting. It has a tabletop with splash back, which can be removed if you wish to use it as an undercounter chiller and add your own tabletop. The legs are adjustable, so it is possible to adapt the height of the table to your needs.

Measures and Content		
Temperature Range	°C	-2 to +8
Climate Class		5
Gross / Net Weight	kg	122 / 112
Gross / Net Volume	l	238 / 190
Design and Material		
Door Number & Type	2 hinged self-closing doors	
Shelves Number & Type	2 wire shelves grey	
Shelf Color	Grey	
Max load on Shelves	kg/m <sup>2</sup>	13
Feet / Legs	4 adjustable legs	
Exterior Finish	SS304	
Interior Finish	SS304	
Lock	No	
Cooling and Functions		
Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic	
Refrigerant	R600a	
Refrigerant Charge	g	95
Thermometer	Yes	
Power and Consumption		
Energy Class	A	
Energy Consumption	kWh/24h	1.03
Annual Energy Consumption	kWh/year	376
Power	13 Amp	
Input Power	W	300
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38
Dimensions		
Internal Dimension (WxDxH)	mm	799 x 580 x 564
External Dimension (WxDxH)	mm	1360 x 700 x 960
Packed Dimension (WxDxH)	mm	1390 x 730 x 1010
40ft Container Load	pcs	48



GN1/1 shelves



Drawers available as separate kit