



- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Internal Volume	m³	11.68
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	825 / 795
Gross / Net Volume	l	

Door Number & Type	1 hinged solid door W:700 H:1765
Max Load on Floor	kg/m ² 2000
Exterior Finish	White
Interior Finish	White
Interior Light	LED
Lock	Yes

Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic, hot gas
Refrigerant	R290
Refrigerant Charge	g200
Thermometer	Yes

Energy Consumption	kWh/24h	31.78
Annual Energy Consumption	kWh/year	11598
Input Power	W	1630
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Internal Dimension (WxDxH)	mm	2160 x 2760 x 1960
External Dimension (WxDxH)	mm	2400 x 3000 x 2200
Packed Dimension (WxDxH)	mm	2500 x 1600 x 2400
40ft Container Load	pcs	4

