

Model:
XPD1850-P-G-LE

Heavy duty triple door display fridge
15 x adjustable shelves, twin vertical mullion mounted LED lighting



General Information

Prodis XPD1850-P-G-LE triple door heavy duty, energy efficient, professional display fridge with vertical LED lighting.



Key Features

Construction


Energy Label

- -1°C to +10°C temperature range
- Forced air refrigeration
- (15) adjustable shelves
- (15) shelf edge ticket strips
- Twin vertical LED lighting
- 1664/1246 litre (gross/net) volume
- 2.38m² display area
- Self closing double glazed doors with Low E treatment
- HMI digital temperature controller
- R290 refrigerant
- 13amp plug in cabinet

- White cabinet exterior
- Grey fronted with aluminium door frames
- White cabinet interior with stainless steel floor for durability
- Low profile aluminium door frames for increased product visibility



Prodis XPD1850-P-G-LE



1975 kWh/annum

2.38 m² 10°C -1°C

Technical Data	
Model	XPD1850-P-G-LE
Color	White exterior, grey Fronted
Door Frame	Low profile aluminium
Glass	Double glazed with low E treatment (outer layer tempered)
Door handle	Full length
Cabinet construction	Painted steel
Gross volume	1664 litres
Net volume	1246 litres
Display Area	2.38m ²
Cabinet dimensions	1880 x 710 x 2003 (w,d,h mm)
Internal dimensions	1790 x 595 x 1568 (w,d,h mm)
Packaged dimensions	1905 x 760 x 2090 (w,d,h mm)
Shelf dimensions	566 x 480mm / 624 x 480mm
Net weight	207.5 kg
Gross weight	235 kg
Heated glass	×
Doors	3
Self closing	✓
Shelves	15 adjustable
Shelf edge ticket strips	✓
Controller	Digital HMI
Door dimensions	615.50 x 1587 (w,d mm)
Lights	Vertical LED mullion mounted
Light power	36w
Light switch	External
System type	Plug-in
Temperature range	-1°C to +10°C
Climate class	4 (30°C; 55%RH)
Refrigerant	R290
Refrigerant charge	130 gram
Compressors	1
Evaporator fans	2
Consender fans	2
Noise level	≤62 dB
Energy consumption	5.41 kWh / 24h
Rated power	700 W
Voltage	220V / 50Hz
Fuse requirements	13amp



Approvals	Available At	Document #