



Gastronorm Fridge Counters

SPCR200P / SPCR300P / SPCR400P

1 Year Parts & Labour Warranty

2-3 Working Days Delivery

UK Service Support



Designed to safely store chilled produce, our SPCR200P (2 doors), SPCR300P (3 doors), and SPCR400P (4 doors) refrigerated counters are perfect for any busy commercial kitchen environment. Constructed from catering grade SS201 Stainless Steel and fitted with a heavy-duty ventilated cooling system this range also features an environmentally friendly R290 refrigerant, 60mm thick insulation, a max ambient of 32°C, fully-automatic defrost system and intuitive digital controls.

Model	Doors	Gross & Nett Capacity		Temperature Range	Energy Consumption	Energy Rating	Dimensions (mm)		
SPCR200P	2	282 ltrs	220 ltrs	-2°C to +8°C	919 kWh per year	C	W1360	D700	H850
SPCR300P	3	417 ltrs	341 ltrs	-2°C to +8°C	1145 kWh per year	C	W1795	D700	H850
SPCR400P	4	553 ltrs	453 ltrs	-2°C to +8°C	1740 kWh per year	C	W2230	D700	H850



Gastronorm Fridge Counters

SPCR200P / SPCR300P / SPCR400P



Range Specifications			
	SPCR200P 2 Door Counter	SPCR300P 3 Door Counter	SPCR400P 4 Door Counter
GTIN Code	5060750321676	5060750321683	5060750322468
Dimensions	W1360 x D700 x H850mm	W1795 x D700 x H850mm	W2230 x D700 x H850mm
Packed Dimensions	W1410 x D750 x H910mm	W1850 x D750 x H910mm	W2260 x D730 x H910mm
Gross/Nett Capacity	282 Litres / 220 Litres	417 Litres / 341 Litres	553 Litres / 453 Litres
Doors	2	3	4
Shelves Supplied	2	3	4
Grid Dimensions	Fits GN1/1 / 333 x 530mm	Fits GN1/1 / 333 x 530mm	Fits GN1/1 / 333 x 530mm
Exterior Finish	SS201 Stainless Steel	SS201 Stainless Steel	SS201 Stainless Steel
Interior Finish	SS201 Stainless Steel	SS201 Stainless Steel	SS201 Stainless Steel
Temperature Range	-2°C to +8°C	-2°C to +8°C	-2°C to +8°C
Max Ambient	32°C	32°C	32°C
Refrigerant	R290	R290	R290
Insulation Thickness	60mm	60mm	60mm
Nett Weight	102kg	121kg	150kg
Energy Rating	C	C	C
Climate Class	4	4	4
Energy Consumption	919 kWh per year 2.517 kWh per 24 hours	1145 kWh per year 3.136 kWh per 24 hours	1740 kWh per year 4.767 kWh per 24 hours
Power Supply	13 amp single phase plug	13 amp single phase plug	13 amp single phase plug
Voltage	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Cooling System	Ventilated	Ventilated	Ventilated
Defrost Type	Automatic	Automatic	Automatic
Reversible Doors	No	No	No
Lighting	No	No	No
Lockable	No	No	No
Castors	Yes	Yes	Yes
Frost Free	Yes	Yes	Yes
Charging Volume	65g	70g	70kg
Compressor Code	NUM60CA1	NUM60CA1	NBC45NA