



Low-Height Outdoor Bottle Coolers

SP1LO-OUT / SP2LO-OUT

2 Years Parts & Labour Warranty

2-3 Working Days Delivery

UK Service Support



The Sterling Pro Low Height Outdoor Bottle Coolers are built for tough outdoor use, featuring corrosion-resistant UV coated steel, waterproof controls, and lockable doors. Available in single or double door models with black or stainless steel finishes, they offer reliable fan-assisted cooling from +2°C to +12°C in ambient temperatures up to 38°C. With internal LED lighting, compact 840mm height, and up to 180 bottle capacity, they're ideal for bars, restaurants, and outdoor service areas.

Model	Doors	Finish	Bottle Capacity	Gross & Nett Capacity		Temperature Range	Energy Consumption	Dimensions (mm)		
SP1LO-OUT-BK	1	Black	106 x 330ml	134 ltrs	116 ltrs	+2°C to +12°C	1.27 kWh/24h	W600	D500	H840
SP1LO-OUT-STSS	1	S/Steel	106 x 330ml	134 ltrs	116 ltrs	+2°C to +12°C	1.27 kWh/24h	W600	D500	H840
SP2LO-OUT-BK	2	Black	180 x 330ml	225 ltrs	185 ltrs	+2°C to +12°C	1.12 kWh/24h	W900	D500	H840
SP2LO-OUT-STSS	2	S/Steel	180 x 330ml	225 ltrs	185 ltrs	+2°C to +12°C	1.12 kWh/24h	W900	D500	H840





Low-Height Outdoor Bottle Coolers

SP1LO-OUT / SP2LO-OUT

Range Specifications				
	SP1LO-OUT-BK	SP1LO-OUT-STS	SP2LO-OUT-BK	SP2LO-OUT-STS
GTIN Code	5060750322550	5060750322567	5060750322581	5060750322574
Dimensions	W600 x D500 x H840mm	W600 x D500 x H840mm	W900 x D500 x H840mm	W900 x D500 x H840mm
Doors	1	1	2	2
Door Type	Hinged	Hinged	Hinged	Hinged
Bottle Capacity	106 x 330ml	106 x 330ml	180 x 330ml	180 x 330ml
Gross Capacity	134 Litres	134 Litres	225 Litres	225 Litres
Nett Capacity	116 Litres	116 Litres	185 Litres	185 Litres
Shelving Included	2	2	4	4
Exterior Finish	Black	Stainless Steel	Black	Stainless Steel
Interior Finish	Aluminium	Aluminium	Aluminium	Aluminium
Temperature Range	+2°C to +12°C	+2°C to +12°C	+2°C to +12°C	+2°C to +12°C
Max Ambient	+38°C	+38°C	+38°C	+38°C
Refrigerant	R600a	R600a	R600a	R600a
Energy Rating	D	D	C	C
Climate Class	4	4	4	4
Daily Energy Usage	1.27 kWh/24h	1.27 kWh/24h	1.12 kWh/24h	1.12 kWh/24h
Annual Energy Usage	465 kWh/year	465 kWh/year	409 kWh/year	409 kWh/year
Power Supply	13 amp plug	13 amp plug	13 amp plug	13 amp plug
Voltage	230V/50HZ	230V/50HZ	230V/50HZ	230V/50HZ
Cooling System	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Defrost Type	Timed	Timed	Timed	Timed
Compressor Mounting	Bottom	Bottom	Bottom	Bottom
Digital Display	Yes	Yes	Yes	Yes
Self Closing Doors	Yes	Yes	Yes	Yes
Reversible Doors	No	No	No	No
Lighting	LED	LED	LED	LED
Lockable	Yes	Yes	Yes	Yes
Castors	No	No	No	No