


Freedom to create


Positive and negative blast chilling, thawing, proofing and retarder-proofer, pasteurization, slow cooking, maintaining the temperature, drying...are just some of the functions that can be managed immediately and precisely, individually or by connecting them in a single flow.



Model: **SBM-061-HA-R290**

Submarine

MULTIFUNCTION, CABINET - 6 x GN 1/1 - 6 x EN1 (600 x 400) - AIR CONDENSING UNIT - GAS R290 ● INTERFACE WITH TOUCH SCREEN CONTROLS AND 7" GRAPHIC COLOUR DISPLAY



CE CB

HOW TO USE

- Core positive blast chilling +90°C/+3°C.
- Freeze maintenance -10°C.
- Refrigerated maintenance +6°C.
- Temperature maintenance +65°C.
- Slow cooking at low temperatures up to +85°C.
- Rising with injection of humidity in the chamber.
- Thawing at controlled temperature and humidity.
- Core flash freezing +90°C/-18°C.

CONTROL MECHANISMS

- 7" touch screen color display with control interface
- Quick-release heated core probe with 4 measuring points
- Control-activated chamber sanitisation system with active ions (HI-GIENE)
- Photo-identifiable processes
- USB connection for uploading and downloading data/recipes
- IoT connectivity as standard
- Water inlet valve.
- Alarm viewing.
- Anti-odour door lock.
- Internal fan stop by micro switch when door is opened.

STRUCTURAL CHARACTERISTICS

- External Scotch Brite satin finish stainless steel
- High density CFC and HCFC-free PU insulation (42 kg/m3).
- Highly ventilated evaporator to ensure the cooling system's maximum efficiency
- Stainless steel internal coating with fully rounded corners
- Die-moulded and leakproof internal base.
- Anti-condensation heating element located on the box under the magnetic seal stop
- Strongbox ergonomic handle
- Magnetic seal on 4 sides of the door
- Indirect-flow electric fans - made of composite material - on the product
- Side guide-supporting uprights with 18 mm-pitch holes
- Compressor-protecting automatic-reset thermal circuit breaker
- Copper-aluminium evaporating coil, cataphoresis-painted
- Copper condensing coil with aluminum fins with high thermal efficiency.
- Patented chamber humidity-injecting system

OPERATION

- Ethernet connection for HACCP Log download and remote service.
- Automatic storage at the end of the blast chilling cycle.
- Multilevel function.
- Drying.
- Cell pre-cooling.
- Automatic defrost cycles.
- Wi-Fi connection for HACCP Log download and remote service.

CLEANING AND MAINTENANCE

- Easy to wash and hygienic safety due to the suspended evaporator coil.
- Easy to clean in accordance with UNI EN 14159 hygiene regulations.

INSTALLATION AND ENVIRONMENT

- Quality ISO 9001 / Safety ISO 45001 / Environmental ISO 14001 certification.
- 100% recyclable packaging.

CONDENSING UNITS

- Automatic defrost and defrost water self evaporating.
- R290 ecological refrigerant gas

STANDARD EQUIPMENT

- Unequipped removable grill-holding panels in AISI 304 18/10 stainless steel, with double "L"-shaped guides
- Quick-release heated core probe with 4 measuring points
- Wi-Fi connection. Compatible with IEEE 802.11g (2.4GHz) standard
- USB connection for uploads and downloads
- Hi-Gene active ion sanitization system

OPTIONAL TO BE REQUESTED WHEN ORDERING

CA-061: Wooden crate packaging

PSX-061: Left hinged door

SKRT-01: Castor kit, 2 with brake

MK051F: Marine version kit - Food zone full AISI 304, flanged feet, anti-tip rack rails


EXTRA ACCESSORIES THAT CAN BE INSTALLED FOLLOWING PURCHASE

TS-061-208-1N-60Hz-HO: 1N-AC 208/230 V - 60 Hz

Capacity				
Capacity	6 x GN 1/1 6 x EN1 (600 x 400)			
No. of layers - h 20	10			
Distance between layers - h 20	mm	35	inch	1.4
No. of layers - h 40	6			
Distance between layers - h 40	mm	52.5	inch	2.1
No. of layers - h 65	5			
Distance between layers - h 65	mm	70	inch	2.8
Minimum layers distance	mm	17.5	inch	0.7
Dimensions				
Width	mm	790	inch	31.1
Depth	mm	820	inch	32.3
Height	mm	900	inch	35.4
Packaging width	mm	830	inch	32.7
Packing depth	mm	920	inch	36.2
Packaging height	mm	1050	inch	41.3
Net weight	kg	110	lbs	242.6
Gross weight	kg	150	lbs	330.8
Volume	m3	0.6	ft3	21.2
Packing volume	m3	0.8	ft3	28.3
Useful Inner Width	mm	670	inch	26.4
Inner depth	mm	435	inch	17.1
PU insulation - Thickness	mm	60	inch	2.4
Technical Data				
Working temperature	°C	+85 / -40 °C		°F NaN
Motor	On board			
Cooling mode	Air			
PU insulation - Thickness	mm	60	inch	2.4
Climate class	5			
GWP - Global Warming Potential	3			
Refrigerant - Type	R290			
Refrigerant - Quantity	g	150	oz	5.29
Power supply				
Power supply voltage	1N-AC 230 V			
Electrical absorption	A	11,74		
Frequency	Hz	50		
Total electric power	kW	1.951		
Cooling power *	kW	1,137		
Heating power	kW	0.5		

Blast chilling			
Blast Chilling Capacity in 90' +90 / +3°C	kg	35	lbs 77.2
Freezing Capacity in 240' +90 / -18°C	kg	25	lbs 55.1
Blast Chilling Capacity in 120' +65 / +10°C - BC standard ISO 22042	kg	30	lbs 66.2
Freezing Capacity in 270' +65 / -18°C - BF standard ISO 22042	kg	20	lbs 44.1
Blast Chilling cycle time - BC standard ISO 22042	min	94	
Freezing cycle time - BF standard ISO 22042	min	266	
Blast Chilling energy consumed - BC standard ISO 22042	kW h / kg	0.062	
Freezing cycle energy consumed - BF standard ISO 22042	kW h / kg	0.221	
Water Connection			
Discharge - ø	mm	50	inch 2.0
Emissions			
Noisiness	db < 70		

* BT - Evap. temp. -25°C / Cond. temp. +45°C



DIMENSIONI mm
DIMENSIONS [in]

- E** CONNESSIONE ELETTRICA
ELECTRICAL CONNECTION
- W** CONNESSIONE SCARICO OPZIONALE
OPTIONAL DRAIN CONNECTION
- H1** CONNESSIONE INGRESSO H2O 1/2"
INLET WATER CONNECTION 1/2"
- H2** CONNESSIONE USCITA H2O 1/2"
EXHAUST WATER CONNECTION 1/2"
- WCS** CONNESSIONE OPZIONALE PER DOCCETTA ESTERNA
CONNECTION OPTIONAL FOR HAND SHOWER