



AN1002BT



UPRIGHT SOLID & GLASS DOOR REFRIGERATION

Description

The reach-in refrigerators feature high grade AISI 304 stainless steel exterior and interior that offers a modern and practical design, which can be further enhanced with an addition of a glass door. The rounded internal corners make clean up easy, allowing for safe fresh meat storage on all solid door units.

LED lighting, adjustable legs and a digital controller with temperature display are only some of the features that make this range worth the investment.



Features

High grade AISI 304 stainless steel exterior & interior

LED internal lighting

Supplied with 3 shelves per door

Rounded internal corners for easy cleaning

Adjustable legs

Replaceable door

Available with double glazed doors

MODEL	DOORS	SHELVES	GROSS CAPACITY	REFRIGERANT	TEMPERATURE RANGE	DIMENSIONS (mm)	ENERGY RATING	POWER USAGE	KWH/ANNUUM	POWER	WEIGHT (kg)
AN501TF	1	3	500L	R290	-2°C / +8°C	H2060 x W687 x D700	C	190W	529	13amp	139
AN1002TF	2	6	1110L	R290	-2°C / +8°C	H2060 x W1385 x D700	B	370W	923	13amp	196
AEX500-TF	1	4	500L	R134a	+2°C / +8°C	H2060 x W687 x D700	-	727W	4015	13amp	161
AEX1000-TF	2	8	1110L	R134a	+2°C / +8°C	H2060 x W1385 x D700	-	1030W	8286	13amp	253
AN501BT	1	3	500L	R290	-18°C / -22°C	H2060 x W687 x D700	D	600W	529	13amp	142
AN1002BT	2	6	1110L	R290	-18°C / -22°C	H2060 x W1385 x D700	D	670W	529	13amp	213
AN501BT-CR	1	4	500L	R290	-18°C / -22°C	H2060 x W687 x D700	-	974W	346	13amp	156
AN1002BT-CR	2	8	1110L	R290	-18°C / -22°C	H2060 x W1385 x D700	-	1744W	637	13amp	244