



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449 R290 R134a**

Name	LUZON 3.75	LUZON 3.13	LUZON 2.50	LUZON 1.88	LUZON 1.56	LUZON 1.25	LUZON 0.94
Code	BA280	BA270	BA260	BA250	BA240	BA230	BA220
Length [mm]	3830	3210	2580	1960	1645	1330	1020
Height [mm]	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10
Depth [mm]	1180	1180	1180	1180	1180	1180	1180
Capacity [dm ³]	729	609	486	366	303	243	183
Display area [m ²]	2,9	2,4	1,9	1,4	1,2	1	0,7
Total Display Area (TDA) [m ²]	-	-	-	-	-	-	-
Temp. range [°C]	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)
Temp. class	-	-	-	-	-	-	-
Climate class	-	-	-	-	-	-	-
Energy efficiency class	D	D	D	D	D	D	E
Refrigerant	R404a / R507 / R448 R449 / R134a / R290	R404a / R507 / R448 R449 / R134a / R290	R404a / R507 / R448 R449 / R134a / R290	R404a / R507 / R448 R449 / R134a / R290	R404a / R507 / R448 R449 / R134a / R290	R404a / R507 / R448 R449 / R134a / R290	R404a / R507 / R448 R449 / R134a / R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	51	43	34	26	22	17	14

Standard equipment

internal cooling aggregate

static cooling

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of white coated steel

storage chamber back doors - hinged (not applicable to corners)

worktop - stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

straight front glass pane (which can slightly be opened)

LED lamp (color of choice: white, confectionery or meaty "deep pink")
bumper - different colors available (IGLOO pattern book)
insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)
automatic defrost
condenser outlet to container
electronic temperature controller with digital display (IGLOO)
condenser impurity or fan operation failure alarm

Options

wooden sides + glass sides - selectable colour (IGLOO colour chart)
device without side panels prepared for multiplexing (MOD/A)
housing with base panel from staff side made of stainless steel
front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)
front panel color - different colors available (IGLOO pattern book)
custom front panel color (after consultation with the IGLOO Sales Department)
base panel made of stainless steel
display space with coloured sheet - selectable colour (IGLOO colour chart)
storage chamber made of stainless steel
exposition area made of acid resistant stainless steel
storage chamber made of acid - resistant stainless steel
exposition area - stepped - 2 steps
exposition area - stepped - 3 steps
powder painted evaporator
night blinds made of plexi glass
worktop - granite grey (thickness - 20 mm)
worktop - granite Balmoral (thickness : 20 mm)
worktop - granite black (thickness : 20 mm)
additional exposition glass shelf
set of wheels (castors)
fans enforcing air circulation
additional LED light in top lamp profile
automatic defrost
device with temperature range from -2 °C to +4 °C (includes electric defroster heaters)
automatic condenser vaporization
analog thermometer
electronic temperature recorder + software
temperature recorder wire
socket with fuse
customer front shelf (aluminum profile anodised color silver or gold)
front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart) (excludes the buffer)
movable partition (low ,glass on stands , placed in exposition area)
top fixed partiton (high , glass in exposition area)
bottom fixed partition (made from stainless steel in storage chamber)
fixed insulated partition panel (increases the module length by 30mm)
runner for small movable table
small movable table for scale or cash register (400x500mm)

