



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Name	LUZON DEEP 0.94	LUZON DEEP 1.25	LUZON DEEP 1.56	LUZON DEEP 1.88	LUZON DEEP 2.50	LUZON DEEP 3.13	LUZON DEEP 3.75
Code	BA220WG	BA230WG	BA240WG	BA250WG	BA260WG	BA270WG	BA280WG
Length [mm]	1020	1330	1645	1960	2580	3210	3830
Height [mm]	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10
Depth [mm]	1180	1180	1180	1180	1180	1180	1180
Capacity [dm ³]	245	325	405	490	650	815	980
Display area [m ²]	0,9	1,1	1,4	1,7	2,3	2,8	3,4
Total Display Area (TDA) [m ²]	0,80	1,06	1,32	1,59	2,12	2,65	3,17
Temp. range [°C]	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)
Temp. class	3H1	3H1	3H1	3H1	3H1	3H1	3H1
Climate class	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)
Energy efficiency class	E	E	E	E	E	E	E
Refrigerant	R290	R290	R290	R290	R290	R290	R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	336,5	382,25	457	470	538,5	828,25	934,75

Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of white coated steel

storage chamber made of white coated steel

rear storage compartment door - hinged (not applicable to corners)

worktop - stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

straight front glass pane (which can slightly be opened)

LED lamp (color of choice: white, confectionery or meaty "deep pink")

bumper - different colors available (IGLOO pattern book)

automatic defrost

condenser outlet to container

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

device prepared for multiplexing

wooden sides + glass sides - selectable colour (IGLOO colour chart)

device without side panels prepared for multiplexing (MOD/A)

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of stainless steel

storage chamber made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid - resistant stainless steel

exposition stepped overlay made of white coated steel (1 step)

exposition stepped overlay made of stainless steel (1 step)

exposition stepped overlay made of acid resistant stainless steel (1 step)

exposition stepped overlay made of white coated steel (2 steps)

exposition stepped overlay made of stainless steel (2 step)

exposition stepped overlay made of acid resistant stainless steel (2 step)

powder painted evaporator

night blinds made of plexi glass

worktop - granite grey (thickness - 20 mm)

worktop - granite Balmoral (thickness : 20 mm)

worktop - granite black (thickness : 20 mm)

additional exposition glass shelf

set of wheels (castors)

additional LED light in top lamp profile

automatic defrost

device with temperature range from -2 °C to +4 °C (includes electric defroster heaters)

automatic condenser vaporization

analog thermometer

electronic temperature recorder + software

temperature recorder wire

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart) (excludes the buffer)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

fixed insulated partition panel (increases the module length by 30mm)

runner for small movable table

