



## EIB-D1015-B1

Black impulse cooler/freezer

### Product Features

- Easily switchable between cooler and freezer
- Temperature Class 3M1/3L1
- Glass sides for better presentation of products
- Ventilated cooling
- LED interior light
- Sliding glass lids
- Ticket strip included
- Controller with Bluetooth and NFC connectivity
- HACCP compliant data export
- Stainless steel bumper bars on all four sides
- Castors, 2 lockable

Versatile impulse chiller/freezer

### Measures and Content

|                    |    |           |
|--------------------|----|-----------|
| Total Display Area | m² | 2.26      |
| Temperature Range  | °C | -18 to +5 |
| Climate Class      |    | 3         |
| Gross / Net Weight | kg | 308 / 278 |
| Gross / Net Volume | l  | 480 / 320 |

### Design and Material

|                   |                          |
|-------------------|--------------------------|
| Lid Number & Type | 2 flat sliding glass lid |
| Castors           | Wheels                   |
| Exterior Finish   | Black RAL9005            |
| Interior Finish   | Black (RAL9005)          |
| Interior Light    | LED Horizontal           |
| Lock              | No                       |

### Cooling and Functions


|                    |                    |
|--------------------|--------------------|
| Type of Controller | Electronic         |
| Type of Cooling    | Ventilated         |
| Type of Defrost    | Automatic, hot gas |
| Refrigerant        | R290               |
| Refrigerant Charge | g149               |
| Thermometer        | Yes                |

### Power and Consumption

| Energy Class              |          | C              |
|---------------------------|----------|----------------|
| Max Ambient               |          | 25°C at 60% RH |
| Energy Consumption        | kWh/24h  | 9.69           |
| Annual Energy Consumption | kWh/year | 3536.85        |
| EEl                       | %        | 32.29          |
| Input Power               | W        | 1251           |
| Voltage / Frequency       | V/Hz     | 220-240/50     |
| Noise Level               | dB(A)    | 54             |

### Dimensions

|                            |     |                    |
|----------------------------|-----|--------------------|
| Internal Dimension (WxDxH) | mm  | 1360 x 790 x 300   |
| External Dimension (WxDxH) | mm  | 1512 x 1010 x 975  |
| Packed Dimension (WxDxH)   | mm  | 1570 x 1070 x 1155 |
| 40ft Container Load        | pcs | 28                 |



Strong handle



Digital controller