

Product specification



HR150/3D: 150 Ltr Undercounter Cabinet Refrigerator

13-106

Three drawer undercounter refrigerator cabinet

Features and benefits

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- High quality magnetic gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Three robust drawers give convenient access to inventory
- Supplied on roller castors as standard for ease of movement and positioning

Refrigerant	R600a	Finish ext/int	S/S & Alu
Temperature	Refrigerator +3/+5°C	Number of sections	3
Electrical supply	230/50/1	Sections Section configuration	1/3
Fuse rating (A)	10		
Current (A)	0.3	System	Integral
Power (W)	65		
Refrigerant mass (g)	65		

Height (mm)	830	Climate Class	4
Width (mm)	605	Energy grade	A+
Depth (mm)	640	EEI	12.51
Gross volume	150	AEC (kWh)	247
(ltr)		Energy	0.678
Net volume (ltr)	73.13	consumption	0.0.0
Leg type	Roller castors rear, levelling	(kWh/24hr)	
	bolts front	GWP	3
Gross weight (kg)	69		
Net weight (kg)	55.5		

Footnotes

• For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.