

Matchbox prep station

Standard drawers + solid worktop



Blast Chill For added functionality a BC option is available with this spec Drawer

Applications

- Highly ergonomic storage solution, right at the point of use
- Matchbox Drawers provide access from both sides of a central island unit
- Ideal for meat, deli and dessert prep
- Perfect storage for garnish and 'mise en place' generally

VCM R2 V1

В

761 Wh/annu

10 5

40°C-40%

*

86L

ENERGY Hydrocarbon R600a Refrigerant Adande Refrigeration Standard drawer 'B' Energy Rating in Freezer Mode 'A' Energy Rating in Fridge Mode (Consumption 307 kWh/annum)



Storage Capacity

Gastronorm (GN) Pans 4 x 1/1 GN 100 mm Deep or equivalent (per Drawer)

Maximum Weight 40 kg of Food (per Drawer)

Volume 86 Litres (per Drawer)

Tested to Climate Class 4 (30°C & 55% relative humidity) for temperature and energy consumption and to **Climate** Class 5 (40°C & 40% relative humidity) for temperature

Mains Supply 230 Vac 50 Hz

Power Socket (included) Correct 2 or 3 Pin Plug fitted for each country

Mains Lead (included) 2 Metre Coiled Lead

Elevation

Standard castors (C) Solid worktop (W) VCM2/CW

2 Drawer matchbox (VCM2)

Options

MATCHBOX + SOLID WORKTOP (W)	High castor base (HC)		Standard castor base (C)		Small castor base (SC)		Rollers & feet base (R)		Small rollers & feet base (SR)		Locking roller base (L)		Small locking roller base (SL)	
Finished height	971 mm	VCM2/HCW	900 mm	VCM2/CW	879 mm	VCM2/SCW	855 mm	VCM2/RW	845 mm	VCM2/SRW	855 mm	VCM2/LW	845 mm	VCM2/SLW
Load-bearing capacity	128 kg		205 kg		430 kg		231 kg		232 kg		204 kg		204 kg	

For full options please see our Drawer Customising and Accessories pages



2 drawer matchbox (VCM2) With open drawer









