

Technical specification

Maxiglass MG3/275CS bottle cooler

MG3/275CS

Maxiglass plug ready glass door bottle cooler



Features and benefits

- The MG3 has been engineered with a fully foamed shell, driving significantly improved temperature performance
- Dimmable LED lights create a beautifully illuminated display area, encouraging impulse purchases
- The MG3 is one of the greenest bottle coolers on the market, with up to 30% energy savings compared to the previous range and R600a environmentally friendly refrigerant as standard
- Innovative flat shelving design ensures no more 'wobbly' bottles, allowing effortless stocking and retrieval of drinks
- Low maintenance condenser design reduces the risk of blockages, meaning that the refrigeration system does not have to work so hard
- Top mounted door locks are supplied as standard, keeping contents safe and secure

Refrigerant	R600A	Door material	Stainless steel
Temperature	Refrigerator +6°C	Finish ext/int	
Electrical supply	220-240V/50/60/1	Hinge	Hinged
Current (A)	1.2	Number of sections	2
Power (W)	185	Section configuration	Left hinge-Right hinge
Refrigerant mass (g)	58	System	Integral
Height (mm)	900	Climate Class	CC2
Width (mm)	1200	Energy grade	D
Depth (mm)	575	EEl	42
Capacity	322 x 330ml bottles 370 x 250ml bottles	AEC (kWh)	628
Gross volume (ltr)	328	Energy consumption (kWh/24hr)	1.72
Gross weight (kg)	103	GWP	3
Net weight (kg)	94	Min - max temperature (°C)	+2/+18

Footnotes

- Height is adjustable from 900 to 910mm
- Allow an extra 10mm to the side of the cabinet for optimal airflow
- Depth of the cabinet is excluding handgrip, including power supply connection

Thank you for your interest in this product. We hope you now have everything you need to choose Gamko, however if you have any further questions, please do not hesitate to contact us.

Gamko, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.gamko.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.