



BAKER SF 1500 CBG

Product series: Baker

Item number: 861540503



The GRAM BAKER SF 1500 CBG is with a net internal volume of 0 Ltr.

Generations of bakeries, confectioners, and patisseries are trusting GRAM BAKER storage and process cabinets to accommodate their bakery products. The GRAM air circulation system is key to maintain correct and uniform temperature and humidity levels inside the cabinet. The air is exhausted and refrigerated before being directed back into the cabinet, circulating around all food items. Thus, unwanted dehydration and skin forming of doughs can be avoided almost entirely.

Preserving Quality

Both storage and process cabinets come with built-in functionalities that preserve the quality of your bakery products at all times.

Low Running Costs

The energy-efficient refrigeration technology implemented in this wide line-up of storage cabinets can help saving running costs on a day-to-day basis.

Built-in Safety

All BAKER Cabinets come with a controller equipped with safety functions: Door alarm, alarms for high-temperature levels, or when the cleaning of the condenser filter is required to avoid overheating. A top panel perfectly protects the controller from water splashes.

Multi-Functional

The SF can be used as a quick chiller/freezer, storage freezer, storage refrigerator, or thawing cabinet. If required, the GA can be also used continuously as a freezer, as a refrigerator, or as a prover.

Designed for Bakers

The GRAM BAKER series strikes with features, specifically designed for the requirements of bakery businesses. The cabinet meets standard bakery tray sizes and the support rails can be individually positioned.

The BAKER SF 1500 CBG comes with the following extras:

- Right-hand hinged door with lock
- Air circulation system
- Dry cooling and controlled thawing (M versions)
- Automatic defrost and reevaporation of water

SPECIFICATIONS

Temperature range	-30/+10°C	Connection load (Watt)	2185
Volume, gross (ltr.)	1422	Climate class	4
Exterior	Stainless	Refrigerant (kg)	0.46
Interior	Stainless	CO2 equivalent (kg)	1.38
Weight, packed (kg)	228	Outside dimensions (W x D x H) (mm)	880 x 1088 x 2465
Insulation (mm)	60 mm (cyclopentane)	Inside dimensions (W x D x H) (mm)	695 x 895 x 1850
Refrigerant	R290	GN or Shelf size	Trayslides 40 x 60 cm
GWP	3	Equipped with	Right hand hinged reversible door with positive handle and lock, stainless and heated floor with drive-in ramp, dry cooling, controlled thawing.
Ref. capacity at -25°C (Watt)	2336	Door Type	Solid Door
Connection	230V, 50 Hz		