TM32

Minibar Cooler

Product Features

- Absorption operated cooling system
- Flat integrated evaporator
- Silent operation
- Low energy consumption
- Reversible solid door
- · Adjustable shelves, also in door
- LED interior light
- Lock





Integrated evaporator

LED light

Silent minibar for hotels

With the TM minibar, your guests can always get a good night's sleep. It has a silent running absorption cooling system classified as 0 dB (A), meaning no disturbance. The minibar has an elegant design with a black exterior and an anthracite interior, which gives that high-end feel. It has internal LED lighting, which turns on when the door is opened.

The cabinet can be fully integrated into the existing décor with a build-in bracket and hinge fixation kit, which allows a joint opening of the cupboard- and minibar door. A hinge fixation kit also secures the stability of the cooler and prevents it from tipping and sliding forward.

| Design and Material | |
|---------------------|---------------------|
| Door No & Type | 1 hinged solid door |
| Door Reversible | Yes |
| Shelves No & Type | 1 wire shelves grey |
| Feet / Legs | 4 adjustable feet |
| Exterior Finish | Black |
| Interior Finish | ABS, RAL7005 |
| Interior Light | LED |
| Lock | Yes |

| Measures and Content | | | | |
|-----------------------|----|------------|--|--|
| Temperature Range | °C | +2 to +12 | | |
| Climate Class | | 3 | | |
| Gross / Net Weight | kg | 17 / 12 | | |
| Gross / Net Volume | I | 29 / 27 | | |
| Cooling and Functions | | | | |
| Type of Controller | | Electronic | | |

| Cooling and Functions | |
|-----------------------|------------|
| Type of Controller | Electronic |
| Type of Cooling | Absorbtion |
| Type of Defrost | Automatic |
| Refrigerant | NH3 |
| Refrigerant Charge g | 70 |

| Power and Consumption | | | | |
|-----------------------|----------|---------------|--|--|
| Energy Class | | G | | |
| Energy Consumption | kWh/24h | 0,62 | | |
| Annual Energy Cons. | kWh/year | 226 | | |
| Input Power | W | 65 | | |
| Voltage / Frequency | V/Hz | 220-240/50-60 | | |
| Noise Level | dB(A) | 0 | | |

| Dimensions | | |
|-------------------------------|-----|-----------------|
| Internal Dimension (WxDxH) | m | 312 x 225 x 395 |
| External Dimension (WxDxH) | mm | 402 x 438 x 500 |
| Packed Dimension (WxDxH) | mm | 450 x 460 x 530 |
| 40ft Container Load | pcs | 384 |