



The Refrigeration Experts

Product specification



LL2/1HDRW: Low Level Counter Refrigerator

14-115

Two drawer reduced width low level refrigerator counter

Features and benefits

- Ideal for quick service restaurants as it provides refrigerated storage under the cooking area
- High performance air distribution system ensures temperature is maintained throughout the counter
- Robust build with heavy duty handles and fixings to withstand constant usage
- Digital microprocessor controller and illuminated on/off switch
- Designed to carry up to 300kg (evenly spread) - invaluable to any cook off station
- Accommodates pans with a depth of up to 100mm
- Supplied with helicoil mains lead, allowing easy movement for cleaning purposes

Technical

Refrigerant	R290
Temperature	Refrigerator +1/+4°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.1
Power (W)	215
Refrigerant mass (g)	120

Build

Finish ext/int	304 S/S & 304 S/S
Number of sections	3
Section configuration	1/2-1/2
System	Integral

Dimensions

Height (mm)	645
Width (mm)	1030
Depth (mm)	800
Gross volume (ltr)	140
Net volume (ltr)	74.4
Leg type	Braked castors
GN size	2/1
Gross weight (kg)	140
Net weight (kg)	106.1

Energy

Climate Class	5
Energy grade	C
EEI	38.58
AEC (kWh)	764
Energy consumption (kWh/24hr)	2.09
GWP	3

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.