

Technical specification

E3/2222MUCS84 bottle cooler

E3/2222MUCS84

Plug ready bottle cooler with 4 solid doors



Features and benefits

- TotalChill technology means there are no hot spots so all bottles and kegs are cooled equally and customers are consistently served cold drinks
- The E3's powerful refrigeration system means you can fill it up and drinks are at the right temperature for the next shift
- Temperature range is adjustable from +2°C to +18°C giving you the flexibility to store white wines, red wines, beers and ciders
- With fantastic energy efficiency and R600a refrigerant as standard, the E3 is the ideal environmentally friendly choice
- Superior storage capacity makes bottling up more efficient for bar staff and allows faster service
- Why not add drawers? A sleek addition which can make the bar layout easier for staff to use

Refrigerant	R600A	Door material	Stainless steel
Temperature	Refrigerator +4/+8°C	Finish ext/int	S/S
Electrical supply	220-240V/50/1	Number of sections	4
Current (A)	1.1	Section configuration	Left hinge-Right hinge-Left hinge-Right hinge
Power (W)	180	System	Integral
Refrigerant mass (g)	70		
Height (mm)	860	Climate Class	CC2
Width (mm)	2542	Energy grade	B
Depth (mm)	512	EEI	17.8
Capacity	722 x 330ml bottles	AEC (kWh)	467
Gross volume (ltr)	687	Energy consumption (kWh/24hr)	1.11
Gross weight (kg)	138	GWP	3
Net weight (kg)	120	Min - max temperature (°C)	+2/+18

Footnotes

- Height is adjustable from 860 to 880mm
- Height without feet is 840mm

Thank you for your interest in this product. We hope you now have everything you need to choose Gamko, however if you have any further questions, please do not hesitate to contact us.

Gamko, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.gamko.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.