

Product specification



FFC2/1: 48 Ltr Counter Vari Temp Drawer

35-107

Variable temperature one drawer reduced width counter

Features and benefits

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works efficiently in hot kitchens, operating in ambient temperatures exceeding ISO Climate Class 5 (43°C ambient)

Technical

Refrigerant R290

TemperatureFreezer

-18/-21°C

Electrical 23

230/50/1

250

supply

Fuse 10

rating (A)

Current 1.5

(A)

Power

(W)

Refrigerant 65

mass (g)

Thermal 200

heat

rejection

(W)

Build

Finish

304 S/S & 304

ext/int

System |

Integral

S/S

Dimensions

Height 600 (mm) Width 775 (mm) Depth 700 (mm) Gross 48 volume (ltr) Net 48 volume (ltr) Leg type Braked castors **Gross** 75 weight (kg) Net 60 weight

Energy

Climate 5 Class С Energy grade EEI 38.69 **AEC** 1029 (kWh) Energy 2.82 consumption (kWh/24hr) 3 **GWP**

Options

Worktop

(kg)

Extended worktop

Footnotes

- Adequate airflow must be kept around the counter: 150mm
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.