



MODEL 530/530A

SOFT SERVE FREEZER

TWIN TWIST, FREE STANDING, DIGITAL CONTROL

Ideal for medium capacity outlets to add soft serve ice cream and frozen yogurt. Innovative design keeps operation simple and helps reduce cost of ownership.





FAST FREEZE DOWN

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption



DIGITAL CONTROL AND DISPLAY

Microprocessor control provides access to system settings and additional functions. Digital interface displays critical info as system status, temperatures, dispense count, errors and so on.



LOW MIX INDICATOR

Light turns "ON" at low mix to alert operator to add mix



SELF CLOSING DISPENSING VALVE

Automatically prevents product overflow after dispense



DISPENSE SPEED CONTROL

Provides flexibility in dispense rate control for different applications



STANDBY

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight



SAFETY PROTECTIONS

- Low temperature and motor overload shut-off to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating

INDUSTRY LEADING SOFT SERVE EQUIPMENT DESIGNED TO THE HIGHEST SPEC FOR QUALITY AND EASE OF USE


MAXIMISE YOUR PROFITS






MODEL 530/530A

SOFT SERVE FREEZER MACHINE







SPECIFICATIONS

Flavours		2 + Twist	
Freezing Cylinders		2 x 1.7L / 1.8qt	
Mix Hoppers		2 x 12L / 12.7qt	
Output Capacity (80 grams)		300 serves/hr	
Clearance Requirements		152mm/6" on back	
WEIGHT	KG/LB (Gravity)	KG/LB (Pump)	
Net	165 / 367	175 / 389	
Shipping	180/400	190 / 422	
Volume	0.90 CBM / 3	1.78 CBF	
DIMENSIONS	NET (MM/IN)	SHIPPING (MM/IN)	
Width	552 / 21.7	660/ 26.0	
Depth	652 / 25.7	830 / 32.7	
Height	1474 / 58.0	1640 / 64.6	

ELECTRICAL	AMPS	VOLTS	POWER(KW)
220-240/50/1	13	NA	NA
208-230/60/1	13	NA	NA

FEATURES

CONTROL SYSTEMS S	SINGLE, DIGITAL
REFRIGERATED HOPPERS	<u> </u>
HOPPER AGITATOR OPTIONAL	✓
TEMPERATURE DISPLAY	~
STANDBY MODE	√
AUTO CLOSING DISPENSING VALVES	V
DISPENSING SPEED CONTROL	V
LOW MIX INDICATOR LIGHT	V
LOW MIX INDICATOR ALARM	V
LOW TEMPERATURE PROTECTION	V
MOTOR AMPERAGE PROTECTION	V
HIGH PRESSURE PROTECTION	V
THERMAL OVERLOAD PROTECTION	\checkmark
S30A: PUMP FEED MODEL, AVAILABLE	\checkmark
AIR PUMP OPTION, AVAILABLE	V
INVERTER SYSTEM	√