



## MD1902X

### Multideck

#### Product Features

- Premium design
- Stainless steel finish
- Mirror effect to interior of end walls
- Adjustable shelves (can be tilted)
- Optional shelf riser
- Vertical LED interior light with switch
- Adjustable feet with rollers to rear
- Night blind / Curtain with soft release
- Fully automatic
- Digital controller and temperature display
- Max shelf weight 50kg per metre

Open front multideck suitable for fresh meat, dairy or c

The TEFCOLD MD-X range of stainless steel multidecks is an ideal "grab and go" choice for shops, cafes, sandwich shops, butchers and convenience stores. At only 680mm deep the unit is ideal where floor space is restricted and you need to maximise refrigerated display area. The units come with base + 4 shelves allowing for excellent storage capacity, which means you can fit up to 5 PET bottles high. A brushed stainless exterior and a mirror finish stainless steel interior helps give a sense of space within the unit while the bright white vertical LED lighting gives excellent illumination inside the cabinet (the MD1902X also has a horizontal LED light across the top). The unit is suitable for display of fresh meat, dairy or drinks and the temperature can be adjusted to suit your requirements. Shelves can be angled between 2 and 20 degrees to give extra merchandising options (shelf risers will be required if shelves are angled). The unit comes fitted with rollers as standard to enable it to be moved out for cleaning, castor are also available as an option. The MD range come in four different widths from 685mm to 1885mm and is also available in a white finish.

Measures and Content		
Total Display Area	m <sup>2</sup>	2.3
Temperature Range	°C	-1 to +5
Climate Class		3
Gross / Net Weight	kg	272 / 243
Gross / Net Volume	l	1314 / 954
Design and Material		
Shelves Number & Type	4 SS304 shelves, tilting	
Shelf Color		Stainless steel
Feet / Legs		2 adjustable feet
Castors		4 rollers
Exterior Finish		Stainless steel
Interior Finish		Stainless Steel
Interior Light		LED
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	2x 105
Power and Consumption		
Energy Class		E
Energy Consumption	kWh/24h	25
Annual Energy Consumption	kWh/year	9125
Power		13 Amp
Max Ambient		25°C at 60% RH
Input Power	W	1250
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	55
Dimensions		
Internal Dimension (WxDxH)	mm	1800 x 560 x 1355
External Dimension (WxDxH)	mm	1885 x 680 x 1985
Packed Dimension (WxDxH)	mm	1970 x 750 x 2140
40ft Container Load	pcs	18



Soft release night blind / curtain



Adjustable shelves with tilting function