



The Refrigeration Experts

Product specification



HR200: 200 Ltr Undercounter Cabinet Refrigerator

13-111

Undercounter refrigerator cabinet

About the product

Convenient, practical and tough Undercounter Cabinets offer compact, on-the-spot storage.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#).

Learn more about our [Undercounter Cabinets](#)

Why choose this product

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- Front breathing, water cooled refrigeration system makes this model suitable for use in enclosed areas
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 40°C (ISO Climate Class 5)

Specification

Technical

Refrigerant

R290

Dimensions

Height (mm)

824

Temperature	Refrigerator +3/+5°C	Width (mm)	684
Electrical supply	220-240/50/1	Depth (mm)	755
Fuse rating (A)	10	Gross volume (ltr)	200
Current (A)	1.2	Net volume (ltr)	95.9
Power (W)	225	Leg type	Roller castors rear, levelling bolts front
Refrigerant mass (g)	116	Gross weight (kg)	67
Thermal heat rejection (W)	240	Net weight (kg)	60

Build

Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral

Energy

Climate Class	5
Energy grade	A+
EEI	13.68
AEC (kWh)	279.94
GWP	3
Energy consumption (kWh/24hr)	0.77

Footnotes

- For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
 +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.