



The Refrigeration Experts

Product specification



RBCT20/60: 60kg /20kg Remote Roll In Blast Chiller and Freezer Cabinet

17-119

Remote roll-in blast chiller cabinet

About the product

Foster Blast Chillers safely control the temperature of produce to ensure that food retains its quality, taste and texture.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [Blast Chiller range](#)

Why choose this product

- Specific model to accept the Rational 201 trolley with a chilling capacity of 60kgs per cycle
- Supplied for connection to remote condensing unit (not included)
- Chilling capacity of 90°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- High quality 304 grade stainless steel finish is food safe and hard wearing
- Operates efficiently in ambient temperatures of up to 43°C

Specification

Technical

Refrigerant

R404a/449a/452a

Electrical supply

230/50/1

Dimensions

Height (mm)

2190

Width (mm)

980

Fuse rating (A)	13	Depth (mm)	865
Current (A)	3.5	Gross volume (ltr)	60
Power (W)	750	Chilling capacity (kg)	60
		Freezing capacity (kg)	20
		Leg type	Feet
		Gross weight (kg)	240
		Net weight (kg)	213

Build Energy

Finish ext/int	304 S/S & 304 S/S	Climate Class	5
Number of sections	1	Freezing capacity (kg)	20
Section configuration	Right hinge		
System	Remote		

Footnotes

- For ventilation and service access ensure that 400mm minimum clearance is allowed above the RBC 20-60
- Requires connection to external drain. 1x 1/2 BSP Drain outlet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
 +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.