



The Refrigeration Experts

Product specification



BCT22/12: 22kg/ 12kg Blast Chiller and Freezer

17-275

22kg Blast chiller/freezer cabinet

About the product

Foster Blast Chillers and Freezers safely control the temperature of produce to ensure that food retains its quality, taste and texture.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [Blast Chiller range](#)

Why choose this product

- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- Freezing capacity from +70°C to -18°C in less than 240 minutes within specifications
- Dedicated 22Kg blast chiller with occasional 12Kg freeze capacity
- Exceeding UK and European food safety requirements
- High grade 304 exterior and interior the 'gold standard' in performance finishes
- Intuitive touch control panel – just press and go!
- 6 Shelf Positions for GN 1/1 Pans

Specification

Technical

Dimensions

Refrigerant	R290	Height (mm)	1515
Electrical supply	230/50/1	Width (mm)	800
Fuse rating (A)	13	Depth (mm)	755
Current (A)	2.4	Gross volume (ltr)	211
Power (W)	550	Net volume (ltr)	105
Refrigerant mass (g)	120	Chilling capacity (kg)	22
		Freezing capacity (kg)	12
		Leg type	Braked castors
		GN size	1/1
		Gross weight (kg)	99
		Net weight (kg)	86

Build

Finish ext/int	304 S/S & 304 S/S	Energy	
Number of sections	1	Climate Class	5
Section configuration	Right hinge	Freezing capacity (kg)	12
System	Integral	GWP	3

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
 +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.