



The Refrigeration Experts

Product specification

FFC4/2: 96 Ltr Counter Vari Temp Drawer

35-105



Variable temperature two drawer reduced width counter

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Available to finance with our award-winning interest-free credit and leasing.

Learn more about our FlexDrawer Counters

Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate - change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works efficiently in hot kitchens, operating in ambient temperatures exceeding ISO Climate Class 5 (43°C ambient)
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table "Temperature" and "Temperature 2"

Specification

Technical		Dimensions
Refrigerant	R290	Height (mm) 900
Temperature	Freezer -18/-21°C	Width (mm) 775
Electrical supply	230/50/1	Depth (mm) 700
Fuse rating (A)	10	Gross volume (ltr) 48
Current (A)	1.5	Net volume (ltr) 48
Power (W)	250	Leg type Roller wheels
Refrigerant mass (g)	65	Gross weight (kg) 138
Temperature 2	Freezer -18/-21°C	Net weight (kg) 130.5
Fuse rating (A) 2	10	Gross volume (ltr) 2 48
Current (A) 2	1.5	
Power (w) 2	250	
Refrigerant mass (g) 2	65	
Thermal heat rejection (W)	400	

Build		Energy
Finish ext/int	304 S/S & 304 S/S	Climate Class 5
Section configuration		Energy grade C
System	Integral	EEI 38.69
		AEC (kWh) 1029
		GWP 3
		Energy grade 2 C
		EEI 2 38.69
		AEC (kWh) 2 1029
		Energy consumption (kWh/24hr) 2.82
		Energy consumption (kWh/24hr) 2 2.82

Footnotes

- Adequate airflow must be kept around the counter: 150mm
- Ecodesign data relevant per compartment
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation - detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.