



The Refrigeration Experts

Product specification



EP700F: 600 Ltr Cabinet Fish Refrigerator

41-232

Single door fish cabinet

About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#) options

Learn more about our [EcoPro G3 range](#)

Why choose this product

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- The EP700F optimises fish storage conditions with the cooling system designed to prevent surface drying of the fish
- Operates efficiently in ambient temperatures of up to 43°C

Specification

Technical	Dimensions
Refrigerant	R290
Temperature	Fish -1/+1°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	2.3
Power (W)	210
Refrigerant mass (g)	80
Thermal heat rejection (W)	190
	Height (mm) 2080
	Width (mm) 700
	Depth (mm) 820
	Gross volume (ltr) 600
	Leg type Braked castors
	GN size 2/1
	Gross weight (kg) 124
	Net weight (kg) 118

Build	Energy
Cabinet type	Fish
Finish ext/int	304 S/S & 304 S/S
Number of sections	1
Section configuration	Right hinge
System	Integral
	Climate Class 4
	GWP 3

Footnotes

- Adequate airflow and service space must be kept above the top of cabinet:
100mm
- Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.