



Temperature range: **+2°C/+15°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290 / R134a**

Name	0.6 2P	0.9 2P	1.3 2P	0.6 3P	0.9 3P	1.3 3P	NZ90 2P	NZ90 3P
Code	CU203.2	CU202.2	CU201.2	CU203.3	CU202.3	CU201.3	CU295.2	CU295.3
Length [mm]	640	940	1340	640	940	1340	-	-
Height [mm]	1200±10	1200±10	1200±10	1400±10	1400±10	1400±10	1200±10	1400±10
Depth [mm]	850	850	850	850	850	850	850	850
Capacity [dm ³]	-	-	-	-	-	-	-	-
Display area [m ²]	1	1,5	2,2	1,1	1,7	2,6	1,1	1,6
Total Display Area (TDA) [m ²]	-	-	-	-	-	-	-	-
Temp. range [°C]	(+2 ± +15°C)	(+2 ± +15°C)	(+2 ± +15°C)	(+2 ± +15°C)	(+2 ± +15°C)	(+2 ± +15°C)	(+2 ± +15°C)	(+2 ± +15°C)
Temp. class	-	-	-	-	-	-	-	-
Climate class	-	-	-	-	-	-	-	-
Energy efficiency class	D	D	D	D	D	E	-	-
Refrigerant	R290	R290	R290	R290	R290	R290	R290	R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	407	447	597	414	454	604	632	646



The presented class applies to selected device modules. The classes for the individual modules may differ. The indication of the energy class for the selected device configuration is given on the attached label.

Standard equipment

internal cooling aggregate R290

external glass elements made of combined glass with argon filling and black silkscreen, white or gray RAL7042

dynamic cooling with automatic defrost

external housing made of coated steel sheet in a colour from the (IGLOO pattern book)

wooden melamine front panel – different colors available (IGLOO pattern book)

ecological polyurethane foam insulation

internal frame painted - different colors available (IGLOO pattern book)

back sliding doors with combined glass (Cube 2 0.6 – hinged doors with choice of door opening direction)

kick plinth made of painted steel (IGLOO pattern book)

glass exposition shelves with height and angle adjustment placed on the frame

bottom shelf made of stainless steel

top internal LED illumination front frame LED illumination

automatic condenser vaporization

electronic temperature controller with digital display

condenser impurity or fan operation failure alarm

Options

device prepared for multiplexing

internal frame made of stainless steel

wooden front panel made of veneer or TREND - different colors available (IGLOO pattern book)

additional each shelf LED illumination

humidity control system

front panel with color-coated sheet - selectable color (IGLOO color guide)

electronic temperature recorder + software

temperature recorder wire

set of wheels (castors)

rear sliding door made of double-glazed units with Venetian mirror (in CUBE 2 0.6 hinged door with Venetian mirror)



