



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Name	MONIKA 2/1.0WG	MONIKA 2/1.3WG	MONIKA 2/1.5WG	MONIKA 2/1.7WG	MONIKA 2/2.05WG	MONIKA 2/2.5WG
Code	MO100WG	MO10WG1	MO102WG	MO103WG	MO104WG	MO105WG
Length [mm]	1060	1300	1500	1700	2040	2520
Height [mm]	1220+/10	1220+/10	1220+/10	1220+/10	1220+/10	1220+/10
Depth [mm]	830	830	830	830	830	830
Capacity [dm ³]	225	281	327	373	451	561
Display area [m ²]	0,55	0,68	0,8	0,91	1,1	1,37
Total Display Area (TDA) [m ²]-	-	-	-	-	-	-
Temp. range [°C]	(+2 ± +8°C)	(+2 ± +8°C)				
Temp. class	-	-	-	-	-	-
Climate class	-	-	-	-	-	-
Energy efficiency class	-	-	-	-	-	-
Refrigerant	R134a / R290	R404a / R507 / R448 / R449				
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	347	350	356	360	474	485

Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of white coated steel

storage chamber made of white coated steel

storage chamber back doors - hinged

worktop - stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

curved front glass openable

LED lamp (colour of choice)

bumper - different colors available (IGLOO pattern book)

insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)

automatic defrost
codenser outlet to container
electronic temperature controller with digital display (IGLOO)
condenser impurity or fan operation failure alarm

Options

housing with base panel from staff side made of stainless steel
front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)
front panel color - different colors available (IGLOO pattern book)
custom front panel color (after consultation with the IGLOO Sales Department)
base panel made of stainless steel
exposition area made of stainless steel
storage chamber made of stainless steel
exposition area made of acid resistant stainless steel
storage chamber made of acid - resistant stainless steel
powder painted evaporator
night blinds made of plexi glass
worktop - granite grey (thickness : 20 mm)
worktop - granite Balmoral (thickness : 20 mm)
worktop - granite black (thickness : 20 mm)
additional exposition glass shelf
delivery overlay for the stainless steel panel front window
set of wheels (castors)
addtional LED light in top lamp profile
automatic defrost
the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)
automatic condenser vaporization
analog thermometer
electronic temperature recorder + software
temperature recorder wire
socket with fuse
customer front shelf (aluminum profile anodised color silver or gold)
movable partition (low ,glass on stands , placed in exposition area)
top fixed partiton (high , glass in exposition area)
bottom fixed partition (made from stainless steel in storage chamber)
runner for small movable table
small movable table for scale or cash register (400x500mm)

